

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.03.2022

Version number 5

Revision: 04.03.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Plaster sealing liquid
- **Article number:** 520 0012 9
- **1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
No further relevant information available.
- **Application of the substance / the mixture:**  
Insulating liquid.  
For separating ceramic materials against plaster.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
bredent GmbH & Co.KG  
Weißenhorner Straße 2  
89250 Senden  
Tel: +49 (0) 7309/872-0  
Fax: +49 (0) 7309/872-24
- **Further information obtainable from:**  
R & D  
e-mail: R.D@bredent.com
- **1.4 Emergency telephone number:** (001) 352 323 3500

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS02, GHS07
- **Signal word** Danger

- **Hazard-determining components of labelling:**

ethyl acetate

- **Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 2)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.03.2022

Version number 5

Revision: 04.03.2022

**Trade name: Plaster sealing liquid**

(Contd. of page 1)

P403+P235 Store in a well-ventilated place. Keep cool.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	50-100%
CAS: 64-17-5 EINECS: 200-578-6	Ethanol Flam. Liq. 2, H225	1-5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.

(Contd. on page 3)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.03.2022

Version number 5

Revision: 04.03.2022

**Trade name: Plaster sealing liquid**

(Contd. of page 2)

See Section 13 for disposal information.

### SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

#### · Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

#### · 7.2 Conditions for safe storage, including any incompatibilities

##### · Storage:

· Requirements to be met by storerooms and receptacles: Store in a cool location.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

##### 141-78-6 ethyl acetate

WEL Short-term value: 400 ppm

Long-term value: 200 ppm

##### 64-17-5 Ethanol

WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

· Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.03.2022

Version number 5

Revision: 04.03.2022

**Trade name: Plaster sealing liquid**

(Contd. of page 3)

**Material of gloves**

Butyl rubber, BR

Recommended thickness of the material:  $\geq 0.5$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

The penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 3).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**

Tightly sealed goggles

### SECTION 9: Physical and chemical properties

**9.1 Information on basic physical and chemical properties****General Information****Appearance:****Form:**

Fluid

**Colour:**

Colourless

**Odour:**

Ester-like

**Odour threshold:**

Not determined.

**pH-value at 20 °C:**

7

**Change in condition****Melting point/freezing point:**

Undetermined.

**Initial boiling point and boiling range:** 77 °C**Flash point:**

-1 °C

**Flammability (solid, gas):**

Not applicable.

**Ignition temperature:**

180 °C

**Decomposition temperature:**

Not determined.

**Auto-ignition temperature:**

Product is not selfigniting.

**Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

**Explosion limits:****Lower:**

2.1 Vol %

**Upper:**

15 Vol %

**Vapour pressure at 20 °C:**

97 hPa

**Density at 20 °C:**0.975 g/cm<sup>3</sup>**Relative density**

Not determined.

**Vapour density**

Not determined.

**Evaporation rate**

Not determined.

**Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

**Partition coefficient: n-octanol/water:**

Not determined.

(Contd. on page 5)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.03.2022

Version number 5

Revision: 04.03.2022

**Trade name: Plaster sealing liquid**

(Contd. of page 4)

· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	89.5 %
<b>Solids content:</b>	10.0 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**
- 141-78-6 ethyl acetate**
- Oral LD50 5,620 mg/kg (rabbit)
- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 6)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.03.2022

Version number 5

Revision: 04.03.2022

**Trade name: Plaster sealing liquid**


(Contd. of page 5)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must be specially treated adhering to official regulations.  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- **14.1 UN-Number**  
· **ADR, IMDG, IATA** UN1993
- **14.2 UN proper shipping name**  
· **ADR** 1993 FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, ETHANOL (ETHYL ALCOHOL)), special provision 640D  
· **IMDG, IATA** FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE)
- **14.3 Transport hazard class(es)**  
· **ADR, IMDG, IATA**  
  
· **Class** 3 Flammable liquids.  
· **Label** 3
- **14.4 Packing group**  
· **ADR, IMDG, IATA** II
- **14.5 Environmental hazards:**  
· **Marine pollutant:** No
- **14.6 Special precautions for user** Warning: Flammable liquids.  
· **Hazard identification number (Kemler code):** 33  
· **EMS Number:** F-E, S-E  
· **Stowage Category** B
- **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.
- **Transport/Additional information:**
- **ADR**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml
- **Transport category** 2
- **Tunnel restriction code** D/E

(Contd. on page 7)

GB



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.03.2022

Version number 5

Revision: 04.03.2022

**Trade name: Plaster sealing liquid**

(Contd. of page 6)

· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN1993, FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, ETHANOL (ETHYL ALCOHOL)), special provision 640D, 3, II

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS02, GHS07
- **Signal word** Danger
- **Hazard-determining components of labelling:**  
ethyl acetate
- **Hazard statements**  
H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.
- **Precautionary statements**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 Store in a well-ventilated place. Keep cool.
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.
- **Department issuing SDS:** R & D
- **Contact:** R & D
- **Abbreviations and acronyms:**  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation

(Contd. on page 8)

GB

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 04.03.2022

Version number 5

Revision: 04.03.2022

**Trade name: Plaster sealing liquid**

(Contd. of page 7)

*ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Flam. Liq. 2: Flammable liquids – Category 2*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

**\* Data compared to the previous version altered.**

GB