Printing date 09.03.2022

Version number 7

Revision: 18.08.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: MKZ Primer, MKZ EM-Aktivator, K-Primer

- · Article number: MKZ02004, APK25003, MKZEM004, MKZ02001
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against:
- No further relevant information available.

• Application of the substance / the mixture: Primer.

· 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: bredent GmbH & Co.KG Weißenhorner Straße 2 89250 Senden Tel: +49 (0) 7309/872-0 Fax: +49 (0) 7309/872-24

Further information obtainable from: R & D
e-mail: R.D@bredent.com
1.4 Emergency telephone number: (001) 352 323 3500

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Remark

The device is a medical device pursuant to Council Directive 93/42/EEC of 14 June 1993 concerning medical devices. No safety data sheet is required for the device, so no claim is made to full compliance with the relevant statutory requirements.

Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

Medical products and medical devices within the meaning of Directives 90/385/EEC and 93/42/EEC used in an invasive manner or in direct contact with the body as well as medical products and medical devices falling under Directive 98/79/EC are fully exempt from the provisions of the CLP Regulation and therefore do not need to be classified, packaged or labelled.

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07
- · Signal word Danger

· Hazard-determining components of labelling:

butanone

P210

- Hazard statements
- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.





Printing date 09.03.2022

Version number 7

Revision: 18.08.2021

Trade name: MKZ Primer, MKZ EM-Aktivator, K-Primer

	(Contd. of page 1)
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361+P353	<i>B IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].</i>
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	<i>F IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</i>
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
· 2.3 Other hazards	
· Results of PBT an	d vPvB assessment
• PBT: Not applicat	ole.
• vPvB: Not applica	ble.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

 Dangerous compon 	ents:	
CAS: 78-93-3	butanone	≤99%
EINECS: 201-159-0	🚸 Flam. Liq. 2, H225	
	 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 	
CAS: 2530-85-0	3-Methacryloyloxypropyltrimethoxysilan	1-5%
EINECS: 219-785-8	🚯 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 85590-00-7	10-Methacryloyloxydecyl dihydrogen phospate	_≤3%
	𝚯 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
· Additional informat	tion: For the wording of the listed hazard phrases refer to section 16	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Rinse out mouth and then drink plenty of water.
- 4.2 Most important symptoms and effects, both acute and delayed

Coughing Dizziness Dizziness

Breathing difficulty

Nausea

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

(Contd. on page 3)



Printing date 09.03.2022

Version number 7

Revision: 18.08.2021

(Contd. of page 2)

Trade name: MKZ Primer, MKZ EM-Aktivator, K-Primer

· Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see item 7.

78-93-3 butanone (≤99	9%)
	Short-term value: 899 mg/m³, 300 ppm
	long-term value: 600 mg/m³, 200 ppm
S	Sk, BMGV
· Ingredients with biolog	gical limit values:
78-93-3 butanone (≤99	9%)
BMGV (Great Britain)	70 μmol/L
	Medium: urine
	Sampling time: post shift
	Parameter: butan-2-one
· Additional information	n: The lists valid during the making were used as basis.

(Contd. on page 4)



Printing date 09.03.2022

Version number 7

Revision: 18.08.2021

Trade name: MKZ Primer, MKZ EM-Aktivator, K-Primer

	Contd. of page 3)
8.2 Exposure controls	
Personal protective equipment:	
General protective and hygienic measures:	
The usual precautionary measures are to be adhered to when handling chemicals.	
Keep away from foodstuffs, beverages and feed.	
Immediately remove all soiled and contaminated clothing	
Wash hands before breaks and at the end of work.	
Avoid contact with the eyes and skin.	
Respiratory protection:	
Not necessary if room is well-ventilated.	
Filter A/P2	
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or low use self-contained respiratory protective device.	nger exposure
Protection of hands:	
The glove material has to be impermeable and resistant to the product/ the substance/ the prepar	
Due to missing tests no recommendation to the glove material can be given for the product/ the the chemical mixture.	preparation
Selection of the glove material on consideration of the penetration times, rates of diffu	sion and the
degradation	
Material of gloves	
Butyl rubber, BR	
Recommended thickness of the material: ≥ 0.7 mm	
The selection of the suitable gloves does not only depend on the material, but also on further ma and varies from manufacturer to manufacturer. As the product is a preparation of several su resistance of the glove material can not be calculated in advance and has therefore to be checke application.	bstances, the
Penetration time of glove material	
The penetration time has to be at least 240 minutes (Permeation according to EN 374 Part 3: Le	
The exact break trough time has to be found out by the manufacturer of the protective gloves of	and has to be
observed.	
Eye protection:	
Tightly sealed goggles	

9.1 Information on basic physical a General Information Appearance:	nd chemical properties	
Form:	Fluid	
Colour:	Colourless	
Odour:	Solvent-like	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling ra	Inge: 79 °C	
Flash point:	-4 °C	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	514 °C	



Printing date 09.03.2022

Version number 7

Revision: 18.08.2021

Trade name: MKZ Primer, MKZ EM-Aktivator, K-Primer

	(Contd. of page 4
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	1.8 Vol %
Upper:	11.5 Vol %
Vapour pressure at 20 °C:	105 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	90.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.
- · 10.3 Possibility of hazardous reactions
- Violent reaction with concentrated alkali and oxidising agents.
- Reacts with peroxides.
- Reacts with strong acids.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

78-93-3 butanone

Oral LD50 3,300 mg/kg (rat)

Dermal LD50 5,000 mg/kg (rabbit)

Primary irritant effect:

- · Skin corrosion/irritation Repeated or permanent exposure may irritate the skin.
- · Serious eye damage/irritation
- Causes serious eye irritation.

• *Respiratory or skin sensitisation Based on available data, the classification criteria are not met.*

(Contd. on page 6)



Printing date 09.03.2022

Version number 7

Revision: 18.08.2021

Trade name: MKZ Primer, MKZ EM-Aktivator, K-Primer

· Additional toxicological information:

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- \cdot Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation
- Must be specially treated adhering to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1193	
14.2 UN proper shipping name		
ADR	1193 ETHYL METHYL KETONE	
IMDG, IATA	ETHYL METHYL KETONE	
Class	3 Flammable liquids.	
Label	3	

bredent

(Contd. of page 5)

Printing date 09.03.2022

Version number 7

Revision: 18.08.2021

Trade name: MKZ Primer, MKZ EM-Aktivator, K-Primer

	(Contd.
14.4 Packing group	
ADR, IMDG, IATA	II
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	F-E,S-D
Stowage Category	В
14.7 Transport in bulk according to Annex II o	of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1193 ETHYL METHYL KETONE, 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture • Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms GHS02, GHS07

· Signal word Danger

- *Hazard-determining components of labelling: butanone*
- · Hazard statements
- H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- *P403+P233 Store in a well-ventilated place. Keep container tightly closed.*
- P403+P235 Store in a well-ventilated place. Keep cool.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t

(Contd. on page 8)

⁻ GB

Printing date 09.03.2022

Version number 7

Revision: 18.08.2021

Trade name: MKZ Primer, MKZ EM-Aktivator, K-Primer

Qualifyin	g quantity (tonnes) for the application of upper-tier requirements 50.000 t	(Contd. of pag
	nical safety assessment: A Chemical Safety Assessment has not been carried out.	
	ON 16: Other information	
	mation is based on our present knowledge. However, this shall not constitute a oduct features and shall not establish a legally valid contractual relationship.	a guarantee for
Relevant j	ohrases	
	hly flammable liquid and vapour.	
	ses skin irritation.	
H319 Cau	ses serious eye irritation.	
H335 May	cause respiratory irritation.	
H336 May	cause drowsiness or dizziness.	
Departme	nt issuing SDS: R & D	
Contact: 1		
Abbreviat	ions and acronyms:	
	nent international concernant le transport des marchandises dangereuses par chemin de fer (Regu	ulations Concerning
	l Transport of Dangerous Goods by Rail)	
	national Civil Aviation Organisation ed relatif au transport international des marchandises dangereuses par route (European Agre	eement Concerning
Internationa	l Carriage of Dangerous Goods by Road)	cement concerning
IMDG: Inter	national Maritime Code for Dangerous Goods	
	ational Air Transport Association	
	lly Harmonised System of Classification and Labelling of Chemicals ropean Inventory of Existing Commercial Chemical Substances	
ELINCS: Eu	ropean List of Notified Chemical Substances	
CAS: Chemi	cal Abstracts Service (division of the American Chemical Society)	
	l concentration, 50 percent	
	l dose, 50 percent ent, Bioaccumulative and Toxic	
	Persistent and very Bioaccumulative	
Flam. Liq. 2	: Flammable liquids – Category 2	
	Skin corrosion/irritation – Category 2	
Eye Irrit. 2: STOT SE 3:	Serious eye damage/eye irritation – Category 2 Specific target organ toxicity (single exposure) – Category 3	
	mpared to the previous version altered.	
co	The case from the provide the second	

